

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED BY

NOV 27 1985

O. C. D.

3a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
3. State Oil & Gas Lease No.	
B-4108	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO TIE BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: P&A		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓		8. Farm or Lease Name Tallmadge
3. Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 2
4. Location of Well UNIT LETTER <u>BG</u> , <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>17S</u> RANGE <u>30E</u> NMPM.		10. Field and Pool, or midcat Loco Hills-Q-G-SA
11. Elevation (Show whether DF, RT, GR, etc.)		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug well as follows:

1. Spot sufficient cement across producing interval to tie back 50' into production casing shoe. Tag plug.
2. Isolate Queen formation from overlying zones with 100' cement plug. Top of Queen is at 2355'; top of cement is at 2204'.
3. Perforate 50' below base of salt at 1208' and squeeze with 50 sx cement, leaving 100' plug in casing. Tag plug.
4. Perforate 50' above top of salt at 410' and squeeze with 50 sx cement, leaving 100' plug in casing. Tag plug.
5. Set 30' surface plug and install regulation abandonment marker.

NOTE: 1) Notify NMOC, ARTESIA, NM, 24 HOURS PRIOR TO BEGINNING WORK.

2) Mud between plugs to be 10#/gallon mud-laden fluid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor DATE 11-26-85

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE DEC - 5 1985

CONDITIONS OF APPROVAL, IF ANY:

DI