

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

R. W. Fair Tyler, Texas
Company or Operator Address
State 30 Well No. 3-A in SW SW NW Sec. 32 T. 17
Locality Loco Hills field, Eddy County.
Well is 2310 feet south of the North line and 4950 feet west of the East line of Section 32
If State land the oil and gas lease is No. B-4108 Assignment No. _____
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is R. W. Fair Address Tyler, Texas
Drilling commenced November 4 19 40 Drilling was completed December 5, 1940
Name of drilling contractor Aston & Fair Address Smith, New Mexico
Elevation above sea level at top of casing 3586 feet.
The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from 1867 to 1868 No. 4, from _____ to _____
No. 2, from 2877 to 2893 No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>8"</u>	<u>28</u>	<u>10</u>	<u>Lapweld</u>	<u>553</u>	<u>Regular</u>				
<u>7"OD</u>	<u>20</u>	<u>8</u>	<u>Seamless</u>	<u>2793</u>	<u>Larkin</u>	<u>Float shoe</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>10</u>	<u>8 1/2</u>	<u>553</u>	<u>50</u>	<u>Halliburton</u>		
<u>8</u>	<u>7"OD</u>	<u>2793</u>	<u>100</u>	<u>Halliburton</u>		<u>5 tons</u>

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
<u>5"</u>	<u>Duplex</u>	<u>Nitroglycerin</u>	<u>40</u>	<u>12-8-40</u>	<u>2888-93</u>	<u>2893</u>

Results of shooting or chemical treatment 150 bbls before shot and approximately 350 bbls after shot.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 0 feet to 2893 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing December 15 19 40
The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

E. A. Sample Driller S. E. Simms Driller
W. J. Cluney Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 10day of December 19 40
SEAL Chas A. Aston

Notary Public

My Commission expires 11-27-43Place Smith, New Mexico Date _____Name E. C. AbstonPosition Office Mgr.Representing R. W. Fair

Company or Operator

Address Citizens Bank Bldg, Tyler, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	230		Shale
230	290		Sand
290	350		Gravel
350	450		Red rock
450	462		Red bed
462	1159		Salt
1159	2355		Anhy
2355	2395		Red sand
2395	2400		Anhy
2400	2410		Lime
2410	2529		Anhy and lime
2529	2555		Sandy lime
2555	2620		Anhy and lime
2620	2677		Shale and shells
2677	2702		Anhy and lime
2702	2874		Lime
2874	2877		Gas sand
2877	2893		Oil sand
2893			Total depth