

OIL CONSERVATION DIVISION

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED BY
NOV 27 1985
O. C. D.
ARTESIA, NEW MEXICO 87501

3a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
3. State Oil & Gas Lease No.
B-4108

SUNDRY NOTICE AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- P&A

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER F, 1650 FEET FROM THE North LINE AND 1650 FEET FROM

THE West LINE, SECTION 32 TOWNSHIP 17S RANGE 30E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3595' GL

7. Unit Agreement Name

8. Farm or Lease Name
Scheurich B

9. Well No.
8

10. Field and Pool, or wildcat
Loco Hills-O-G-SA

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug well as follows:

1. Spot sufficient cement across producing interval to tie back 50' into production casing shoe. Tag plug.
2. Isolate Queen formation from overlying zones with 100' cement plug. Top of Queen is at 2356'; top of cement is at 2349'.
3. Perforate 50' below base of salt at 1200' and squeeze with 50 sx cement, leaving 100' plug in casing. Tag plug.
4. Perforate 50' above top of salt at 408' and squeeze with 50 sx cement, leaving 100' plug in casing. Tag plug.
5. Set 30' surface plug and install regulation abandonment marker.

NOTE: 1) Notify NMOC, ARTESIA, NM, 24 HOURS PRIOR TO BEGINNING WORK.

2) Mud between plugs to be 10#/gallon mud-laden fluid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Granita Doolittle

TITLE Production Supervisor

DATE 11-26-85

APPROVED BY Mike Williams

OIL AND GAS INSPECTOR

DATE DEC - 5 1985

CONDITIONS OF APPROVAL, IF ANY

DI