(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Les	Cru	ces
Lease No	0289	38	(a)
Unit	<u>D</u>		

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SH	HUT-OFF SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR R	REPAIR WELL SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIE	DIZE SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER	
NOTICE OF INTENTION TO ABANDON WELL	L
(INDICATE ABO	OVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	July 10 , 19_
oolley	I man of (N) is a man of (E).
'ell No 12-D is located	d 330ft. from $\binom{N}{S}$ line and 330ft. from $\binom{F}{W}$ line of sec. 35
2 N/1 NW2 Sec. 33	17 S 30 E N.M.P.M. (Twp.) (Range) (Meridian)
Premier	Eddy New Mexico
(Field)	(County or Subdivision) (State or Territory)
	DETAILS OF WORK
	DETAILS OF WORK sective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceming points, and all other important proposed work)
We will abandon of spth of 3256' and no ater in this well. A	DETAILS OF WORK ective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceming points, and all other important proposed work) our Woolley 12-D, it was drilled to a total oil was found in the Premier Pay. There was 10 sack cement bridge was set at 3100°, hol to base of salt, we put a 10 sack cement plat 245°, filled to top and 5 sack cement
We will abandon on the plan of 3256 and no ater in this well. A lied with heavy mud a top of 8 5/8 stub and 4 pipe marker for	DETAILS OF WORK sective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceming points, and all other important proposed work) our Woolley 12-D, it was drilled to a total oil was found in the Premier Pay. There was 10 sack cement bridge was set at 3100°, hol to base of salt, we put a 10 sack cement plat 245°, filled to top and 5 sack cement remarker. Streceive approval in writing by the Geological Survey before operations may be commenced. Woolley
We will abandon to object the state names of and expected depths to object the state of 3256 and no ater in this well. A lied with heavy mud top of 8 5/8" stub and 4" pipe marker for I understand that this plan of work must company Roland Rich	DETAILS OF WORK sective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceming points, and all other important proposed work) our Woolley 12-D, it was drilled to a total oil was found in the Premier Pay. There was 10 sack cement bridge was set at 3100', hol to base of salt, we put a 10 sack cement plat 245', filled to top and 5 sack cement r marker. streeeive approval in writing by the Geological Survey before operations may be commenced. Woolley