

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Carper Drilling Company

Artesia, New Mexico

Company or Operator

Address

Koenig

Well No. 1

in SW $\frac{1}{4}$ NW $\frac{1}{4}$

of Sec. 28

T. 17

Lease

R. 30

N. M. P. M.,

Grayburg-Jackson

Field,

Eddy

County.

Well is 1980 feet south of the North line and 660 feet west of the East line of 26-17-30

If State land the oil and gas lease is No. B-2384

Assignment No.

If patented land the owner is , Address

If Government land the permittee is , Address

The Lessee is Carper Drilling Company

Address Artesia, New Mexico

Drilling commenced August 27

19 43

Drilling was completed October 22

19 43

Name of drilling contractor

Address

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3250' to 3258'

No. 4, from to

No. 2, from 3303' to 3310'

No. 5, from to

No. 3, from 3335' to 3345'

No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 440' to feet.

No. 2, from 3310' to 3318' feet.

No. 3, from 3345' to 3357' feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8"	28#	8	Hall.	525'	Tex.-Pattern			
7"	20#	8	Hall.	3201'	Tex.-Pattern			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8"	525'	50	Halliburton		
8"	7"	3201'	50	Halliburton		4 tons mud

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 8 feet to 3400' feet, and from feet to feet

PRODUCTION

Put to producing, 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

M. A. Lapsley

Driller

Dell M. Walter

Driller

Guy Seward

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Artesia, New Mexico

October 25, 1943

Place

Date

Subscribed and sworn to before me this 25th

day of October, 19 43

Name

Stanley Carper

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30	30	Caliche
30	85	55	Red Beds
85	170	95	Red Rock
170	225	55	Red Bed
225	300	75	Gyp
300	320	20	Red Rock
320	370	50	Anhydrite
370	400	30	Grey Lime
400	450	50	Anhydrite
450	495	45	Red Bed
495	525	30	Anhydrite
525	870	345	Salt
870	880	10	Anhydrite
880	1215	335	Salt Salt
1215	1255	40	Anhydrite
1255	1395	140	Salt
1395	1560	165	Anhydrite
1560	1775	15	Lime
1575	1580	5	Anhydrite
1580	1650	70	Anhydrite
1650	1670	20	Red Rock
1670	1760	90	Anhydrite
1760	1775	15	Lime
1775	1980	205	Anhydrite
1980	1983	3	White Lime
1983	2040	57	Anhydrite
2040	2058	18	Lime
2058	2275	217	Anhydrite
2275	2294	19	Lime
2294	2315	21	Anhydrite
2315	2335	20	Lime
2335	2365	30	Anhydrite
2365	2370	5	Brown Shale
2370	2386	16	Anhydrite
2386	2408	22	Anhydrite & Red Shale xx
2408	2495	87	Anhydrite
2495	2511	16	Lime
2511	2590	79	Anhydrite
2590	2615	25	Red Sand
2615	2655	40	Lime
2655	2671	16	Anhydrite
2671	2709	38	Lime
2709	2719	10	Anhydrite
2719	2757	38	Lime
2757	2762	5	Red Rock
2762	2900	138	Anhydrite
2900	2909	9	Lime
2909	2920	11	Brown Sandy Shale
2920	2962	42	Anhydrite
2962	3303	341	Lime
3303	3318	15	Water Sand
3318	3341	23	Grey Sand
3341	3347	6	Grey Sand & Lime
3347	3365	18	White Lime
3365	3369	4	Sand
3369	3380	11	White Lime
3380	3395	15	Lime