Submit 3 Copies to Appropriate ate of New Mexico	C/ S Form C-103
District Office Energy, Minerals and Natural Resources Department	31-115-124451 Revised 1-1-88
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION	WELL API NO. Permit # A-10974
DISTRIC II P.O. Box 2088 P.O. Drawer DD, Artesia, NM 88210 Sante Fe, New Mexico 87504-2088	Indicate Type of Lease STATE
DISTRICT III 1000 Rio Bratots Rd, Azlec, NM 87410	6. State Oil & Gas Lease No. B-2384
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	7. Lease Name or Unit Agreement, Name Grayburg Jackson Unit 2 3 4 5 6 7
1. Type of Well: OIL X GAS WELL WELL OTHER	Amoco State
Pendragon Energy Partners, Inc.	8. Well No. (3)
2 Address of Ossista	9. Pool name or Wildcat 33 DCD ARTESIA
621 17th St., Suite 750, Denver, CO 80293	7. Footballe of Wildeat 1922 South Million State
4. Well Location	Feet From The West
Section 36 (SW-NW) Township 17S Range 30E	. Eddy
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT I	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPP	vs.
PULL OR ALTER CASING CEMEN	PLUG AND ABANDONMENT [X
OTHER OTHER	
12. Describe Proposed or Completed Operations (Clearly name all pertinent details, and give pertinent dates, including estimated date of Abandonment History:	
February 1, 2001: Set CIBP @ 2950' and spot 10 sxs plug on top.	Plug #3 35 sxs cmnt 550
	to surface w/marker
February 2, 2001: Spot 25 sxs cement @ 2470'. Tag cement top	8 5/8" casing
@ 1100'.	@ 525' cmntd to 0'.
: Spot 25 sxs cement @ 2470'	Plug #2:
: Tag cement top @ 1110'.	25 sxs cement @ 2470' -1110'.
: Spot 35 sxs cement @ 550' to surface	
w/ marker.	7" scab liner from 2420-3200'.
Note: All equipment and debrie will be removed from the leastion and	
Note: All equipment and debris will be removed from the location and	Plug #1
the surface restored to original conditions. Reseeding will be	CIBP @ 2950' w/
done according to State specifications.	10 sxs cement.
	4 1/2" casing @ 3424' w/ +/- 100 sxs
I hereby certify that this information shown is true and complete to the best of my knowledge and belief.	
SIGNATURE AGENT	DATE April 16, 2001
TYPE OR PRINT NAME John Luchetta	
(This space for State Use)	
APPROVED BY Phil Hlewkin TITLE Field Ryp. I	DATE _5/14/208/