

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

API# 30-015-4451

NO. OF COPIES RECEIVED	
DISTRIBUTION	<input checked="" type="checkbox"/>
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED

Re-Entry

JUL 18 '88

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2130-6	
7. Unit Agreement Name	
8. Farm or Lease Name Amoco	
9. Well No. 1	
10. Field and Pool, or Wildcat Grayburg-Jackson SR-QGSA	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

O.C.D. ARTESIA, OFFICE

Name of Operator

GENERAL OPERATING COMPANY

Address of Operator

c/o H & S Oil Company, Suite 303, First Natl. Bank Bldg.-Artesia, NM

Location of Well

UNIT LETTER C 1980 FEET FROM THE West LINE AND 660 FEET FROM

THE North LINE, SECTION 36 TOWNSHIP 17S RANGE 30E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☒  
PLUG AND ABANDONMENT ☐  
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Logging - 3389 TD  
Previous 8 5/8" Casing-found top plug @ 380' and bottom @ 550'  
Ran 85 jts. of 10.5# 4 1/2" Casing to 3390'. Cemented with 986 sacks  
Howco Lite, 15# Salt 1/4# Flo Seal, and 250 sacks premium plus 3/10 of 1#  
CFR-3 with 6# Salt.  
Circulated 180 sacks to pit, plug down at 6:30 AM

Atlas wireline perfs at 3296-3353 - 13 holes  
Acidized with 1000 Gal. - Fraced with 20,600 Gal 30# Gel, 13,000# 20/40 Sand,  
8000# 12/20 Sand

Perforate 3233-3238 - 5 holes  
Fraced with 12,000 Gal 30# Gel, 70 sx 20/40 Sand, 40 sx 12/20 sand.

Perforate 3016-3106-17 holes  
Fraced with 30,000 Gal 30# Gel, 30,000# Sand

16. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Williams

TITLE Agent

DATE 7/14/88

Original Signed By  
Mike Williams

JUL 19 1988

APPROVED BY Oil & Gas Inspector  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE