

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Bratons Rd, Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-04453

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No. B-2130-6


7. Lease Name or Unit Agreement, Name

Grayburg Jackson  
Amoco State

8. Well No.

1

9. Pool name or Wildcat



SUNDY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS)

Type of Well:

OIL ☒ GAS ☐  
WELL WELL OTHER

Name of Operator

Pendragon Energy Partners, Inc.

Address of Operator

621 17th St., Suite 750, Denver, CO 80293

Well Location

Unit Letter 660 Feet From The North Line and 660 Feet From The East

Section 36

Township 17S

Range 30E

NMFM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3597' Grd

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

WELL OR ALTER CASING ☐

OTHER ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☒

2. Describe Proposed or Completed Operations (Clearly name all pertinent details, and give pertinent dates, including estimated date of starting proposed work) SEE RULE 1103

**Abandonment History:**

January 29, 2001: Set CIBP @ 2997' and spot 10 sxs cement on top.

January 31, 2001: Spot 25 sxs cement @ 1150'.

: Spot 40 sxs cement @ 575' to surface w/  
marker.

Note: All equipment and debris will be removed from location and  
the surface restored to original conditions. Reseeding will  
be done according to State specifications.

**Plug #3:**

40 sxs cement to  
surface w/ marker.

8 5/8" casing @ 525'  
cemented to surface

**Plug #2:**

25 sxs cement from  
1150-1500'.

4 1/2" casing @ 3395'  
w/ +/- 100 sxs cement

**Plug #1:**

CIBP @ 2997' w/  
10 sxs cement on top.

I hereby certify that this information shown is true and complete to the best of my knowledge and belief.

SIGNATURE

John Luchetta

TITLE

Agent

DATE

April 15, 2001

TYPE OR PRINT NAME

(This space for State Use)

APPROVED BY

Phil Hawkins

TITLE

Field Rep I

DATE

5/14/2001