

30-015-04456

W7X R-2032

RECEIVED BY

Form 9-331

Dec. 1973

FEB 24 1986

O. C. D.

ARTESIA OFFICE

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Page 1

Form Approved.

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other **X-Water Injection Well**

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: **1650' FNL & 2537' FWL**AT TOP PROD. INTERVAL: **Same**AT TOTAL DEPTH: **Same**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☒(other) **Plug & Abandon**

5. LEASE

LC 028936-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal L

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Loco Hills-Queen-Grayburg-San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

31 - 17S - 30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3565' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up pulling unit; tripped out of hole with tbg and packer.
2. WIH with tbg and circulated hole with 10# brine and salt gel mud.
3. Spotted 40 sx Class H cement with 5% CaCl from 2740' to 2260'; TOH.
4. WIH w/perf gun after 2 hrs & tagged top of plug @ 2738' - (lost plug).
5. WIH w/tbg & spotted 50 sx Class H cement from 2738' to 2130'; TOH. (Plug covers top Gbg).
6. WIH w/perf gun after 2 hrs & tagged top of plug @ 2150'; pulled up & perforated 4 squeeze holes @ 1132' (100' below Salt section).
7. WIH w/cement retainer & set @ 1000'. Cement squeezed w/30 sx Class H cement @ 600#psi. Squeezed 19 sx (230') out perfs & left 11 sx (130') below retainer. (This plug covers bottom of Salt section).
8. Pulled tbg up to 830' and spotted 25 sx Class H cement from 830' to 500' (across hole in casing @ 753' (this plug repairs hole in casing); TOH.
9. WIH with perf gun after 12 hrs & tagged top of plug @ 489'; pulled up and perforated 4 squeeze holes @ 465' (50' above Salt Section).

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mike Brumwell TITLE Field Foreman DATE June 22, 1984

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 2.21.86
CONDITIONS OF APPROVAL, IF ANY: