

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

MINERAL CONSERVATION

Form Approved
Budget Bureau No. 42-R1424

c/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☒ other **X-Water Injection Well**

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: **1650' FS & ELs**

AT TOP PROD. INTERVAL: **Same**

AT TOTAL DEPTH: **Same**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) **Plug & Abandon**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Rigged up pulling unit and went in hole with tubing.
2. Circulated hole with 10% brine and salt gel mud.
3. Spotted 25 sx Class C cement with 4% CaCl from 2790' to 2405'; TOH.
4. WIH with perf gun and tagged top of plug @ 2530'; pulled up & perf 4 squeeze holes @ 1240' (100' below salt section).
5. WIH with tubing and spotted 25 sx Class C cement with 4% CaCl from 1250' to 865'; squeezed 10 sx cement out squeeze holes; TOH.
6. WIH with perf gun and tagged top of plug @ 1010'; pulled up and perforated 4 squeeze holes @ 393' (50' above salt section).
7. WIH with tubing and spotted 25 sx Class C cement with 4% CaCl from 430' to 45'; squeezed 10 sx cement out squeeze holes; TOH.
8. Tagged top of plug @ 180'.
9. WIH with tbg & spotted Class C cement from 120' to surface; TOH; RDPU.
10. Cut off all casing & anchors below surface; set P&A marker; cleaned & leveled location.
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mike Brumwell TITLE Field Foreman DATE February 15, 1984

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Note: Mud consisting of 10% brine with salt gel was used between all plugs.

Post ID-3
3-16-84
p+H

5. LEASE

LC028936-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal M

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Loco hills-Queen-Grayburg-San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

31 - 17S - 30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3562' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED BY

MAR 12 1984

O. C. D.

ARTESIA, OFFICE