

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IT
(Other inst
verse side)PLICATED
IONS ON REForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 031844

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Fren Oil Co. A

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T17S, R31E

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 435' FEL (Unit Letter P)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4023' CTF

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has been shut in since 1968 when production became 100% water. No remedial possibilities exist. We propose to P & A as shown below:

Set 30 sx cement from 3600-3740'

Shoot off & recover 7" from free point (estimate top of cement @ 2900')

Set 30 sx cement in & out of 7" stub

Set 30 sx cement across 8-5/8" shoe @ 965'

Set 10 sx cement in top of well

Will use gel mud to spot all plugs. 8-5/8" casing will remain intact. Location will be cleared & leveled.

RECEIVED

SEP 3 1971

18. I hereby certify that the foregoing is true and correct.

SIGNED

A. D. Hatcher

OFFICE

Dist. Drlg. Supervisor

DATE

9/3/71

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

SEP - 7 1971

H. L. BECKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side