


N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Green Bay Co &amp; Dominion Oil &amp; Gas Co

Roswell, New Mexico

Company or Operator  
State 1 Well No. 1 in NW-NE $\frac{1}{4}$  of Sec. 2, T. 17  
Address  
Lease  
R. 31, N. M. P. M., Robinson Field, EDDY County.  
Well is 330 feet south of the North line and 1980 feet west of the East line of See 2, T 17-R31  
If State land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_  
If patented land the owner is \_\_\_\_\_ Address \_\_\_\_\_  
If Government land the permittee is \_\_\_\_\_ Address \_\_\_\_\_  
The Lessee is \_\_\_\_\_ Address \_\_\_\_\_  
Drilling commenced Dec 31, 1940 19 \_\_\_\_\_ Drilling was completed March 12, 1941 19 \_\_\_\_\_  
Name of drilling contractor Brewer Drilling Co Address Artesia, New Mexico  
Elevation above sea level at top of casing \_\_\_\_\_ feet.  
The information given is to be kept confidential until Nil 19 \_\_\_\_\_

## OIL SANDS OR ZONES

No. 1, from None to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from 3563 to 3605 No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from 3555 to 3575 No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 2973 to 3010 feet. 37 red sand  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>8<math>\frac{1}{2}</math></u>	<u>28</u>	<u>8</u>	<u>Wheeling</u>	<u>867</u>	<u>reg</u>				<u>Salt string</u>
<u>7</u>	<u>20 OD</u>	<u>8</u>	<u>"</u>	<u>3250-5</u>	<u>reg</u>				<u>Oil string</u>

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>10</u>	<u>8<math>\frac{1}{2}</math></u>	<u>867</u>	<u>50</u>	<u>Halliburton</u>	<u>none</u>	<u>None</u>
<u>8</u>	<u>7</u>	<u>3250-5</u>	<u>100</u>	<u>#</u>		<u>5 tons</u>

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		<u>None</u>				

Results of shooting or chemical treatment None

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from 0 feet to 4005 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## PRODUCTION

Put to producing Dry 19 \_\_\_\_\_  
The production of the first 24 hours was \_\_\_\_\_ barrels of fluid of which \_\_\_\_\_ % was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be \_\_\_\_\_  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

Truman Jacobs Driller O. C. Bean Driller  
W. I. Owen Driller A. E. Early Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 19day of March 19 41

Notary Public  
My Commission expires \_\_\_\_\_

1941 Roswell, New Mexico 3-19-41  
Place Date

Name V. B. L. KentPosition ContractorRepresenting Brewer Drilling Co  
Company or OperatorAddress Box 506 Artesia, N.M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	725	725	Red rock & sand
725	870	145	Anhydrite
870	1840	970	Salt
1840	2973	1133	Anhydrite
2973	<del>XXXX</del> 3010	± 37	Red sand 6 B W per hour
3010	3030	20	Anhydrite
3030	3121	98	Lime
3121	3400	279	Anhydrite
3400	4005	605	Lime Total depth