NEW MEXICO OIL CONSERVATION COMM. SION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

triplicate to the Oil Conservation Commission or its proper agent within ten days after the letted. It should be signed and sworn to before a notary public for reputation beginning.

Regulations of the Commission.		sworn to before a notary public for report test of casing shut-offs, result of pluggs witnessed by an agent of the commission. notary public. See additional instructions	ing of well, and Reports on minor o
	Indicate nature of	report by checking below:	
REPORT ON BEGINNING DRILLING OF	PERATIONS	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OF TREATMENT OF WELL	R CHEMICAL	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASSHUT-OFF	SING	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING O	F WELL X		
OIL CONSERVATION COMMISSION Santa Fe, New Mexico Gentlemen:	N,	sia, New Mexico March 18-1	
Green Bay Co. & Dominio	n Oil & Gas Co	s obtained under the heading noted above a State Well No. 1 Lease	in the
NW-NE of	Sec		, N. M. P. M.,
Robinson	Field, E D]	Ο Υ	County
The dates of this work were as fol	lows: March	12 & 13th -1941	
Notice of intention to do the work wand approval of the proposed plan w	vas (was not) subm vas (was not) obtair	itted on Form C-102 on ned. (Cross out incorrect words.)	19
	COUNT OF WO	RK DONE AND RESULTS OBTAINED	•
Ran 15 sacks of cement then ran 15 sacks cement cement-filled hole to before testing and foun of cement- Casing record: Pulled 407' 6" of 8\frac{1}{4} c Pulled 2174'3" of 7" c	in bottom of at and filled a 800 feet with ad hole dry. Fi	hole- and filled with mud to 31 with mud to 1800 feet- then ran mud and ran 15 sacks cement- le illed hole to bottom of cellar a le left 460° in hole.	00 feet- ten sacks of: t set 48 hours
Ran 15 sacks of cement then ran 15 sacks cement cement-filled hole to before testing and foun of cement- Casing record: Pulled 407: 6" of 84 c	in bottom of at and filled a 800 feet with ad hole dry. Fi	hole- and filled with mud to 31 with mud to 1800 feet- then ran mud and ran 15 sacks cement- le illed hole to bottom of cellar a le left 460° in hole.	00 feet- ten sacks of: t set 48 hours

Remarks:

OIL & GAS INSPECTOR