HEW MEXICO OIL CONSERVATION COMMISSION RECEIVED C-103 MISCELLANEOUS REPORTS ON WELLS SEP 3 0 1960 (Submit to appropriate District Office as per Commission Rule 1106) Name of Company Address Mid-Century Oil and Gas Company 833 San Jacinto Building, Houston 2, Texas Well No. Unit Letter Section Township Range Tidewater-State of New Mexico M -17 South 31 East Date Work Performed Pool County 9-20-60 Robinson Eddy THIS IS A REPORT OF: (Check appropriate block) Beginning Drilling Operations X Casing Test and Cement Job Other (Explain): Plugging Remedial Work Detailed account of work done, nature and quantity of materials used, and results obtained. Ran and cemented 119 joints of 5-1/2" J-55, 15.50#, Short T&C, J & L Seamless casing with Baker Float Collar and Guide Shoe with Baffle Plate as follows: Guide Shoe 1.36 1 Joint 5-1/2" Casing 32.12 Float Collar 1.45 118 Joints 5-1/2" Casing 3712.47 Rotary space to Kelly Bushing 10.60 Casing set at 3758, 001 Cemented with 100 Sacks regular cement and 25 sacks Latex by Halliburton Oil Well Cementing Company. Witnessed by James I. Wood Company Mid-Century Oil & Gas Co. Position Pet. Eng. J. B. Koonce Tool Pusher Forster Drilling Company FILL IN BELOW FOR REMEDIAL WORK REPORTS ONLY ORIGINAL WELL DATA D F Elev. T D PBTD Producing Interval Completion Date Tubing Diameter **Tubing Depth** Oil String Diameter Oil String Depth Perforated Interval(s) Open Hole Interval Producing Formation(s) RESULTS OF WORKOYER Water Production Oil Production Gas Production GOR Gas Well Potential Date of Test BPD MCFPD BPD Cubic feet/Bbl MCFPD Before Worko ver After Workover I hereby certify that the information given above is true and complete to the best of my knowledge. OIL CONSERVATION COMMISSION

Position

Company

Owner

Mid-Century Oil and Gas Company

Approved by

OIL AND GAS INSPECTOR

Title

Date

No. Copies Received On 1818ULCAL				
		1773 F	at ^d e .	
OPERATOR .		1		
SACAN N		f		
PROSERVE CHICL				
STATE LAIL COLOR				
Ū, 5. ω. S				,
TRACEDION.				
FILE		*	1	
SUATNE DE MINES			. * · • • ·	*