

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN ☐ LOCATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029426 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H. E. West "B"

9. WELL NO.

26

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

3-T17S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Water Injection	2. NAME OF OPERATOR SINCLAIR OIL CORPORATION Sinclair Oil & Gas Company	3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980 feet from the South Line and 660 feet from the East Line of Section 3-T17S-R31E	5. DATE OCT 1 1968	6. EFFECTIVE DATE Effective March 4, 1969
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3968' GR		16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) **Plugback, perf. acidized, Water** ☒ **Fraced**
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) **Converted to WIW**REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 3-16-66 Set C.I. Bridge Plug @ 3690'. Jet perforated Grayburg 3422-27', 3458-63', 3473-78', 3485-90', 3546-51', 3563-68', 3574-79' w/ 70 - 3/8" holes.
- 3-17-66 M. A. washed Grayburg perforations 3422-3579' w/1750 gals. (spotted 1st 100 gals. over perms.) using 86 ball sealers Max. Press. 2800#, Min. 2300# @ 3.1 BPM. ISIP 2400#, 5 mins. SIP 2300#.
- 3-18-66 Water Sand Frac Grayburg perforations 3422-3579' w/35000 gals. gelled water, and 35000# 20/40 sand plus 80 ball sealers. Max. Press. 5600#, Min 3600# @ 15 BPM. Inst. SIP 2900#, 10 mins. SIP 2500#, 12 hours SIP 1350#.
- 3-21-66 Injected 200 bbls. fresh water into Grayburg thru perforations 3422-3579' in 6 hrs. Max. Press. 120#. Converted to Water Injection Well in West Waterflood Area effective 3-21-66.

RECEIVED

RECEIVED
APR 1 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Superintendent**DATE **3-31-66**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

APPROVED
APR 6 1968
RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEEROrig&cc: USGS, Artesia
cc: Regional Office
cc: file

*See Instructions on Reverse Side