

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other P & A

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL, Sec. 4-17S-31E

5. Lease Designation and Serial No.

LC-029426-B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

H. E. West "B" #7

9. API Well No.

30-015-05071

10. Field and Pool, or Exploratory Area

Grayburg Jackson

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -----

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was to be converted to water injection.

4/22/96 to 4/30/96 - Drilled, had metal in returns. Tagged fish @ 3541', unable to drill out. Shut in.

We were unable to drill junk out of hole, so this well was plugged and abandoned as follows:

6/3/97 to 6/4/97 - Set cement retainer @ 3035' & squeezed open hole w/335 sxs Class "C" cmt. Stung out of retainer & left 10 sx on top of retainer. Spotted 9.5# mud from 2900' to 1400'.

6/5/97 to 6/6/97 - Ran CBL from 2941'-900', TOC @ 1130'. Perf'd 4 squeeze holes @ 695'. Pumped 200 sxs Class "C" @ 695', circ'd 7" x 8 5/8" annulus w/cmt. Circ'd 115 sxs to pit. Spotted 50' surface plug. Installed dry hole marker. Filled cellar w/cement.

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers

Karen Byers

Title Engineering Technician

Date 6/10/97

(This space for Federal or State office use)

Approved by (ORIG. SGD.) ALEXIS C. SWOBODA

Title PETROLEUM ENGINEER

Date JUN 10 1997

Conditions of approval, if any: