

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Repollo Oil Company

Hobbs, New Mexico

Company or Operator

Address

J. L. Keel

Well No. 3

in SE SW

of Sec. 7

T. 17

R. 31

N. M. P. M.

Artesia

Field,

New Mexico

County.

Well is 330 feet north of the north line and 1650 feet east of the east line of Section 7

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced April 20 19 38 Drilling was completed June 16 19 38

Name of drilling contractor Address

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 3498 to 3575 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	28#	8		531	TP				
7"OD	24#	10		3092	Float				
2"	4/6#	Reg. 25 Tubing		3512					

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8"	338	50	Halliburton		
	7"OD	3100	100	Halliburton		6 ton

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	None					

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3575 feet, and from feet to feet

## PRODUCTION

Put to producing 7-1 19 38

The production of the first 24 hours was 185 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

J. T. Henry Driller O. T. Mays Driller

Geo. Kiffmeyer Driller Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

Place

Date

day of 19

Name F. Brett

Position Dist. Supt

Notary Public

Representing Repollo Oil Company

Company or Operator

My Commission expires

Address Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	300		Sand, Red rock and Red bed
300	450		Red rock
450	530		Anhy and red rock
530	745		Salt
745	1280		Salt and anhy
1280	2758		Anhy
2758	3575		Lime
3575			Total depth