

NMOCC UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
verse side)TE
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029435 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAY - 7 1980

7. UNIT AGREEMENT NAME

ARTESIA, OFFICE

8. FARM OR LEASE NAME

J. L. Keel "A"

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Wildcat Paddock
Grayburg Jackson11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

7-17S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3702' GR

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug & Abandon

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Rigged up, installed BOP, RIH w/2-7/8" tbg OE to 4657'. Spotted 35 sx Cl C cmt cont'g 4% gel 4657-4535'. POH w/tbg. Spotted heavy gelled mud between plugs. RIH w/cmt retr, set @ 2675'. Cmdt thru retr w/100 sx Cl C cmt cont'g 4% gel. MP 1250#, 1050# standing pressure. Dumped 3 sx cmt on top of retr. RO 5 sx cmt. Perf'd 7" csg w/4 JSPF @ 1210'. RIH w/cmt retr, set @ 1155'. Cmdt thru retr w/100 sx Cl C cmt cont'g 18% salt & 2% CaCl. MP 1300#, stdg press 800#. Dumped 3 sx cmt on top of retr. RO 5 sx cmt. Perf'd 7" csg @ 650' w/4 JS. Circ thru 7" csg & 10-3/4" csg ARO 2-1/2 BPM @ 150# w/very small returns. RIH w/7" cmt retr, set @ 596'. Cmdt thru retr w/200 sx Cl C cmt cont'g 18% salt, 2% CaCl. MP 250#. Dumped 3 sx cmt on top of retr. RO 3 sx cmt. Cmt did not circ. Pmpd 200 sx Cl C cmt down 10-3/4" csg. First 100 sx on vac, second 100 sx standing full of cmt. Installed regulation dry hole marker, cleaned & leveled location. P&A eff 5/31/78.

POSTED
7 D 9
APR 30 1980
RECEIVED
JUN 5 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Drlg. Supt.

DATE 6/2/78

(This space for Federal or State office use)

APPROVED BY (Sgd) GEORGE H. STEWART

DISTRICT ENGINEER

DATE MAY 05 1980

CONDITIONS OF APPROVAL, IF ANY: