

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other Water Injection Well
2. NAME OF OPERATOR ARCO Oil & Gas Co.
Division of Atlantic Richfield Company
3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, New Mexico 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL (Unit Ltr "E")
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

(other) Move pkr, return to single WIW per OCD

5. LEASE
LC-029435(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

MAY - 7 1980

8. FARM OR LEASE NAME

J. L. Keel "B"

O. C. D.

9. WELL NO.

17

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Grayburg Jackson QGSA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

8-17S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3738' GR

RECEIVED

MAY - 2 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- On 4-23-80 rigged up, POH w/pkr & 2-3/8" OD tbg.
- RIH w/salta lined tbg & Model R pkr. Circ 2-3/8"x4 1/2" annulus w/corrosion inhibited water, set pkr @ 2919'. Pressured up on 4 1/2" csg to 600# for 30 mins. OK.
- Connected up well head for single water injection well into Grayburg Jackson perfs 2965-3601'. Returned to single water injection well on 4-24-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Sr. Dist. Prod Super.

DATE

4-30-80

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

ACTING DISTRICT ENGINEER

MAY 05 1980

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: