

Copy to SR

DEPARTMENT OF THE INTERIOR, BUREAU OF
GEOLOGICAL SURVEY

ORDER NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ New Well ☐ Other Plug & Abandon

2. NAME OF OPERATOR:

Richfield Company

3. ADDRESS OF OPERATOR:

P. O. Box 1710, Hobbs, New Mexico 88400

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
Give township and range if known.)

5. DEPTH OF WELL (Unit letter D)

6. DATE OF REPORT

7. ELEVATION (Show whether of, to, or, on, etc.)

3302' GR

8. LEASE DESIGNATION AND SERIAL NO.

LC 029423 (5)

9. IS INDIAN, ALLOTTEE OR TRIBE LAND?

10. UNIT AGREEMENT NAME

11. FARM OR LEASE NAME

H. E. West "L"

12. WELL NO.

3

13. FIELD AND POOL, OR ANNUAL

Grayhawk Shale & Sandstone Q-G-3A

14. SUB, CL, PL, OR BEH AND
SUCCEED OR AREA

9-178-311

15. COUNTY OR PARISH

Eddy

16. NOTES

None

17. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

☐ PULL OR ALTER CASING
☐ MULTIPLE COMPLETS
☐ ABANDON*
☐ CHANGE PLANS

☐ WATER SHUT-OFF
☐ FRACTURE TREATMENT
☐ SHOOTING OR ACIDIZING
(Other) Plug & Abandon

☐ REPAIRING WELL
☐ ALTERING CASING
☐ ABANDONMENT*

(Note: Report results of multiple completion or well
Completion or Recompletion Report and Log Form)

18. SUMMARY OF OPERATIONS (Clearly state all pertinent facts, and give pertinent dates, including estimated date of starting and
reporting work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per-
mitted by this work.)

TD 1111', PCD 8443'. Present perfs 2100'-2231' Seven Rivers.

Plugged & abandoned in the following manner:

- On 2/2/78 ran 7" cmt retr on 2-7/8" OD tbg & set retr @ 1744'. Rmptd 123 sx Cl C cmt
cont'g 4% gel, max & final pump press 1400#. Pld tbg up to 1684' & RO 6 sx cmt. Left
60' cmt on top of retr @ 1744'. TOC @ 1684'. FOH w/tbg & stinger.
- Perf'd 4 - 1/4" holes in 7" csg @ 700'.
- Run 7" cmt retr on 2-7/8" tbg, set retr @ 557'.
- Core 3-5/8" X 7" annulus w/175 sx Cl C cmt w/10% salt & 2% CaCl. Circ 15 sx cmt out.
Marked top of cmt @ 507' (50' above retr @ 557').
- Spotted 10 sx inside 7" csg @ surface, installed regulation dry hole marker, cleaned
& leveled location in accordance w/land management stipulations. P&A eff 6/7/78.

Your office to be notified when location is ready for final inspection.

19. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Dist. Engr. Supv.

DATE 6/7/78

(This space for Federal or State office use)

APPROVED BY _____
CONDITION OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*Use backsheet on Reverse Side

POSTED
ID-2
P&A
4-1-77