

Copy to SF
" Eng.Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 029395(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "A"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT
SURVEY OR AREA
Grayburg-Jackson11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T17S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FNL, 660' FWL (Unit Letter D)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3733' Grd

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run 4½" Innerstring

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

MI & RU plg unit 12/8/69. Ran 114 jts of 4½" 9.5# Midco-50 ST&C 8R Class I csg w/guide shoe, float collar & 4 centralizers = to & set @ 3497.91'. Cemented 4½" csg w/200 sx Class C cmt. Plug down @ 8:35 PM 12/12/69. WOC 36 hrs. Tested 4½" csg to 1300# for 30 min. Held OK. (Top of cement behind 4½" csg @ 1020' by temperature survey.) Perforated w/one 0.42" JS @ 3364, 3365, 3373, 3384, 3389, 3393, 3402, 3404, 3407, 3412, 3413, 3427, 3433, 3434, 3440, 3444, 3452, 3453, 3459, 3462, 3466, 3467, 3468, 3478, 3480, 3484, 3486 & 3489 (28 holes). Treated perms w/3500 gallons 15% LSTNE HCl acid & ball sealers. Ran 2" injection string w/Johnson 101-S tension pkr set @ 3291'. Job complete @ 10:00 Am 12/16/69. Returned well to injection service.

RECEIVED
DEC 19 1969

RECEIVED

DEC 23 1969

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. Ditcher

TITLE

Dist. Drlg. Supervisor

DATE

12/17/69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES
DEC 22 1969
District Engineer
ACTING

*See Instructions on Reverse Side