

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other last page on reverse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "B"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT
Grayburg-Jackson11. SEC., T., R., M., OR BLK. AND
SURVEY OF AREA

Sec. 20, T17S, R31E

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P.O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FNL, 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3666' Grd.

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☒REPAIR WELL ☐

(Other) Run 4½" Inner String

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to run an inner string of 4½" OD 8R 9.5# C-55 ST-20 casing to T.D. and cement w/150 sx of salt saturated Class "C" cement. Perforate the Jackson zone w/one 0.42" jet shot at 3300, 3302, 3304, 3310, 3312, 3322, 3324, 3326, 3328, 3333, 3345, 3349, 3352, 3357, 3359, 3395, 3398, 3403, 3412, 3413, 3419, 3421 and 3424 (23 holes, GR-N log). Treat w/3000 gallons of 15% HCl acid and ball sealers. Run 2-3/8" tubing w/packer set at 3225', load annulus w/treated fresh water and resume water injection. Work will start about 12/8/69.

RECEIVED

NOV 26 1969

J. C. C.
ARTESIA, OFFICE

RECEIVED

NOV 25 1969

U. S. GEOLOGICAL SURVEY
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. Litcher

TITLE

Dist. Drlg. Supervisor

DATE

11-24-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side