

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN (Other inst. verse side) F ATE*Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "B" (B)

9. WELL NO.

45

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 20-17S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ Plug & Abandon

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

2080' FEL & 660' FSL (Unit letter O)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3699' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Plug & Abandon

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 4/6/75 rigged up & installed BOP. RIH w/bit & csg scraper to 3250' PBD. POH w/bit & scraper. WIH & rev sd to top of RBP @ 3280'. Rec BP. WIH w/cmt retr on tbg & set @ 3095'. Pumped & displaced 70 sx Cl C cmt w/ 4% gel below retr & left 5 sx on top of retr. Pulled up hole w/tbg & circ hole w/9# mud. POH w/tbg. Cut 5½" csg @ 770'. Pld csg 25', unable to work free. Cut 5½" csg @ 610' & POH. RIH w/tbg to 660', unable to go deeper. Spotted 80 sx Cl C cmt 660-320' across 5½" csg stub, 8-5/8" csg shoe & top of salt. Spotted 10 sk cmt plug 25' to surface. Installed regulation dry hole marker. P&A effective 4/10/75.

Note: Your office to be notified before final cleanup of location regarding possible additional requirement that pad and/or road be ripped & re-seeded.

RECEIVED

APR 17 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Drlg. Supv.

DATE 4/15/75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

JUN 10 1975

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

posted
ID-2
6-13-75