

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Injection2. NAME OF OPERATOR
GETTY OIL COMPANY3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Ltr. L., 1650' FSL & 1980 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Collapsed Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☒
☐
☐
☐
☐5. LEASE
LC-029420

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Skelly Unit

8. FARM OR LEASE NAME

9. WELL NO.
6710. FIELD OR WILDCAT NAME
Grayburg-Jackson11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 21, T17S, R31E12. COUNTY OR PARISH
Eddy13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3771' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/17-19/81 Ran bit and scraper. Tag scale @ 3022. Cleaned out to 3557'.
2/20/81 Ran tubing and packer to 3541'. Spotted 475 gals. Xylene. Let set 1½ hrs. Spotted 475 gals. 15% NE. Treated open hole 3280-3557 with total of 3000 gals. Maximum pressure 1300#, min 1200#, ISIP 600#, rate 5.3 BPM. Pulled packer, ran B.P., set @ 3253'. Set packer @ 2969'. Treated perms from 3077-3237 with 1500 gals. 15% NE. Maximum pressure 2300#, min. 2300#. Released plug and packer.
2/23/81 Pulled and laid down 2 7/8 work string plug and packer. Ran Howco R-4 tension packer on 2 3/8 tubing. Set packer @ 2983'. Rigged down unit.
2/24/81 Injecting 150 bbls. @ 200#.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE Area Superintendent

DATE 3/2/81

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAR 10 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO