

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Company Hobbs, New Mexico
Company or Operator Address
Lea #B# Well No. 1 in NE SE of Sec. 25, T. 17
R. 31 N. M. P. M. Maljamar Field, Eddy County.
Well is 3300 feet south of the North line and 660 feet west of the East line of section 23.
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Skelly Oil Co. Address Tulsa, Oklahoma
The Lessee is Skelly Oil Co. Address Tulsa, Oklahoma
Drilling commenced September 23, 1940 Drilling was completed November 23, 1940
Name of drilling contractor Sahara Drilg. Co. Address Monahans, Texas
Elevation above sea level at top of casing 3531 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3473 to 3870 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4	40#	8	LM	600'	3"				
7"	20#	10	SS	3244'					
Tubing									
2" EUE	4.7#	8	SS	3875'	10"				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	10 3/4	600'	100	Halliburton	Circulated back to cellar	
8 7/8"	7"	3223'	200	Halliburton		
Tubing 2"		3875'	Swung			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from top feet to 3290 feet, and from feet to feet

PRODUCTION

Put to producing November 24, 1940
The production of the first 24 hours was 84 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Ba
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

R. M. Jones Driller Ira Jiant Driller
Paul Critton Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30 Hobbs, New Mexico November 29, 1940
day of November 1940 Name J. N. Dunevey
SEAL L. E. Nelson Notary Public Position District Superintendent
Representing Skelly Oil Company
My Commission expires December 10, 1940 Address Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	75		Sand
75	180		Red rock
180	155		Gravel
155	180		Lime
180	425		Red shale , blue shale
425	465		Red rock
465	510		Red lime
510	587		Anhy
587	605		Red shale
605	640		Anhy
640	663		Lime
663	668		Red shale
668	680		Anhy
680	705		Red shale
705	1875		Salt, anhy, potash
1875	1895		Red rock
1895	2420		Anhy
2420	2450		Anhy Lime
2450	3210		Anhy
3210	3880		Lime
3880			Total depth