

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

FEB 04 1983

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water-injection		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Texas American Oil Corporation		5. State Oil & Gas Lease No. B-8095
3. Address of Operator 300 W. Wall - Suite 400 Midland, Texas 79701		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>E</u> , <u>1370</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>17</u> RANGE <u>30</u> NMPM.		8. Farm or Lease Name Etz State
15. Elevation (Show whether DF, RT, GR, etc.) 3687'		9. Well No. 10
		10. Field and Pool, or Wildcat Grayburg-Jackson
		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spot 20 sx. cement 2090'-1870' - Tag plug @ 1781'.
Perf 2 holes @ 1075', Spot 50 sx. plug. Tag plug @ 847'.
Perf 2 holes @ 603', spot 40sx. plug. Tag plug @ 498'.
Pumped 90 sx. cement down 7" bradenhead.

7" csg. @ 561' w/50sx.
2 7/8" tbgs. @ 2078' w/100 sx.
T.D. 2095'

Prep to install dry hole marker.

Post ID-2
2-11-83
P4A

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rekenson TITLE Monahans District Mgr. DATE February 3, 1983

APPROVED BY Larry Brooks TITLE Geologist DATE 4/22/83

CONDITIONS OF APPROVAL, IF ANY: