

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL CONS COMMISSION
ower DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Marbob Energy Corporation

3. Address and Telephone No.

P.O. BOX 227, Artesia, NM 88210 (505) 748-3303

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL Sec 13 T-17-S R-29-E Unit E

5. Lease Designation and Serial No.

LC-028 784-C

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NMNM88525X

8. Well Name and No.

Burch Keely Unit #16

9. API Well No.

30-015-20339

10. Field and Pool, or Exploratory Area

Grbg Jackson SR Q GRBG

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) 4 1/2 CIBP @ 2455' Cap with 35' cement 2-4-92
- 2) Load hole with mud
- 3) Perforate 4 1/2 casing @ base of salt 926' Squeeze with 50 sacks cement W.O.C.
Tag cement top @ 821'
- 4) Perforate 4 1/2 casing @ top of salt 525' Squeeze with 50 sacks cement W.O.C.
Did not tag cement Re-squeeze with 50 sacks cement W.O.C
Tag cement top @ 378'
- 5) Perforate 4 1/2 casing @ 60' Circulate cement to surface between 4 1/2, 8-5/8 & open hole with 35 sacks
- 6) Job completed 10-30-95

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Elvira K. Kileck

Title District Secretary

Date 11-2-95

(This space for Federal or State office use)

Approved by Orig. Signed by Shannon J Shaw

PETROLEUM ENGINEER

Conditions of approval, if any:

Title

Date 12/8/95