

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instruction
verse side) CATE*
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028784-a

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely A

9. WELL NO.

17

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., MG. OR BLK. AND
SURVEY OR AREA

Sec. 13, T-17-S; R-29-E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
General American Oil Company of Texas

3. ADDRESS OF OPERATOR
P. O. Box 416, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' PSL and 1980' ^{FEL} of Sec. 13, TWP. 17-S; RGE. 29-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3620 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Well Spudded at 2:00 P.M. 1/26/71.
2. Ran 407'KB of 8 5/8" 20" Casing as follows:
 - a. Volume of cement equalled 132 cubic feet (100 Sacks).
 - b. Brand of cement was Southwestern Class C with 2% CaCl.
 - c. Approximate temperature of cement slurry 60° F.
 - d. Formation temperature 65° F.
 - e. After standing cemented for 9 hours compressive strength was 800#. Pressure tested to 400#. Tested OK.
 - f. Drilled out cement after standing 12 hours.
3. Ran 3155'KB of 4-1/2" 9.5" Casing and cemented with 250 sacks of cement.
4. We perforated as follows: 3 holes (2489-2490); 2 (2492-93); 8(2524-28); 8(2531-35); 5(2558-61); 10(2925-90); 9(2973-76); 8(3001-03); 8(3055-58); 6(3089-91).
5. We sand fraced the Matex Sand with 40,000 gals. water and 40,000# sand. The San Andres was acidized with 8250 gals. 15% Acid.

RECEIVED

1971

RECEIVED
FEB 19 1971
FEDERAL BUREAU OF
SURVEY

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

DATE Feb. 18, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD PURPOSES

FEB 22 1971

Date

ACTING

District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to State law and regulations, either are shown below or will be issued by or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement of otherwise depths (top and bottom) and method of placement of cement plugs; and or other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date/well site conditioned for final inspection leading to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229
847-485

[illegible]