

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0467933

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dale H. Parke "B" Tract "C"

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson, Q., S.A.

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Section 15, T-17S, R-30E

12. COUNTY OR
PARISH

Bddy

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL
WELL ☐GAS
WELL ☐DRY ☐

Other

b. TYPE OF COMPLETION:

NEW
WELL ☒WORK
OVER ☐DEEP-
EN ☐PLUG
BACK ☐DIFF.
RESVR. ☐

Other

2. NAME OF OPERATOR

Shenandoah Oil Corporation

3. ADDRESS OF OPERATOR

1500 Commerce Building, Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1980 FNL & 1980 FNL, Sec. 15, T-17S, R-30E

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

2/15/72

16. DATE T.D. REACHED

2/22/72

17. DATE COMPL. (Ready to prod.)

3/1/72

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3,705 GR.

19. ELEV. CASINGHEAD

3,704'

20. TOTAL DEPTH, MD & TVD

3,459'

21. PLUG, BACK T.D., MD & TVD

3,452'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

Rotary

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

Grayburg: 2,885-2,889'; 2,873-2,880'; 2,773-2,781'

25. WAS DIRECTIONAL
SURVEY MADE

yes

26. TYPE ELECTRIC AND OTHER LOGS RUN

Dual Laterolog - B.H. Compensated Density Log

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	20	422'	12 1/4	200 sacks	
5 1/2	14	3,452'	7 7/8	400 sacks	
2 3/8 tubing		2,850'			

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PERFORATION RECORD (Interval, size and number)

Grayburg: 2,885-89' (8 holes)
2,873-80' (14 holes)
2,773-81' (16 holes)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2,873-89'	500 gal. 15% NE acid, 20,000# sand
2,773-81'	20,000 gal. gelled water (Same as Above)

33.*

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
3/1/72		Pumping 2" x 1 1/2" x 8' insert				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
3/2/72	24		→	120	166.8	30	1,390
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
		→				36	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Venting - Pending connection from Continental

TEST WITNESSED BY

C. W. Downey, Jr.

35. LIST OF ATTACHMENTS

(1) Dual Laterolog (2) BEC Pa-Density

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

T. P. Bates

TITLE

Vice President

DATE

March 6, 1972

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Surface	0	270		Base Salt	1,125	+2,580
Red Beds, Anhyd. & Salt	270	1,125		Yates	1,300	+2,405
Anhyd. & Gyp.	1,125	1,300		Queens	2,195	+1,510
Anhyd. w/sand & sh. stringers	1,300	2,195		Grayburg	2,570	+1,135
Sand	2,195	2,225		San Andres	2,905	+ 800
Anhyd. w/sand stringers	2,225	2,570				
Lime, Anhyd., & sand	2,570	2,905				
Dolomite w/sand stringers	2,905	3,459 T.D.				