

Form 9-331
Dec. 1973

6-USGS-Roswell
1-PS-Engr.
1-LC-Foreman
1-File

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ Injection Well
2. NAME OF OPERATOR
Getty Oil Company /
3. ADDRESS OF OPERATOR
P.O. Box 730 Hobbs, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit Ltr. N 660' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
OCT 7 1981
(NOTE: Report results of multiple completion or zone change on Form 9-330.)
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
LC-029418 (b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
OCT 8 1981
8. FARM OR LEASE NAME
Lea "C" O.C.D.
9. WELL NO.
9 ARTESIA, OFFICE
10. FIELD OR WILDCAT NAME
Grayburg-Jackson
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 11, 17S-31E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3942 DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/8/81 - Rigged up Permian Well Service. Backflowed well.
9/9/81 - POH w/tubing and packer.
9/10/81 - RIG w/bit and scrapper. Cleaned out to T.D. Circulated hole clean.
Ran Arrow treating packer and set at 3887'.
9/11/81 - Rigged up Knox Services. Spotted 500 gals. 15% NE FE @ 3887'. Set packer at 3338'. Pumped 2,000 gals. acid over perms 3369-3878' using 40 ball sealers. Flushed w/32 bbls. Formation broke at 4200#; Maximum pressure 4200#, minimum pressure 2100#. ISIP 2200#, 5 min. SIP 1900#, 10 min. SIP 1750#, 15 min. SIP 1650#. Ran 5 1/2" Baker AD-1 Pkr. on tubing. Circulated hole w/100 bbls. treated water and set packer @ 3295' w/14,000# tension.
9/12/81 Nipped up injection line and rigged down.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Pale R. Crockett TITLE Area Superintendent DATE October 1, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE OCT 7 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO