

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI ATE*
(Other instruction. on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-028793-6

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burch C

9. WELL NO.

28

10. FIELD AND POOL, OR WILDCAT

Grayburg- Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T17S, R30E

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General American Oil Co. of Texas

3. ADDRESS OF OPERATOR

P. O. Box 416, Loco Hills, N. M. 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FSL & 1980' FEL, Sec. 30, T17S, R30E

RECEIVED

14. PERMIT NO. AUG 2 1972

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3595 GL

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

ARTESIA, OFFICE

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Well spudded at 12:00 noon 6-13-72.

2. Ran 505' KB of 8-5/8" 20# casing as follows:

a. Volume of cement equalled 132 cubic feet (100 sacks)

b. Brand of cement was Southwestern Class C with 2% CaCl.

c. Approximate temperature of cement was 70°.

d. Formation temperature was 86°.

e. After standing cemented for 9 hours compressive strength was 800#.

Pressure tested to 400#. Tested OK.

f. Drilled out cement after standing cemented 12 hours.

3. Ran 3425' KB of 4-1/2" 9.5# casing and cemented with 450 sacks cement.

4. We perforated as follows: 2734'-41', 2787'-92', 2849'-54', 2890'-93', 2945'-49', 2984'-88', 3166'-74', 3350'-54', 3401'-05'

5. Acidized from 3401'-3405' with 2,000 gallons.

Acidized from 3350'-3354' with 2,000 gallons.

Fraced from 3166'-3174' with 30,000# sand and 30,000 gallons water.

Fraced from 2945'-2988' with 20,000# sand and 20,000 gallons water.

Attempted to treat 2849'-2893' and communicated.

Acidized from 2787'-2792' with 2250 gallons.

Fraced from 2734'-2741' with 30,000# sand and 30,000 gallons water

RECEIVED
AUG-11-1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Superintendent

DATE 7-31-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

AUG 2 1972

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.