

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028793-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burch "C"

9. WELL NO.

30

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T-17S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 416 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' FSL and 622' FWL, Sec. 30, T-17S, R-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3593' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Well spudded at 12:00 noon 6-11-72.

2. Ran 512' KB of 8-5/8" 20# casing as follows:

a. Volume of cement equalled 132 cubic feet (100 sacks)

b. Brand of cement was Southwestern Class C with 2% CaCl.

c. Approximate temperature of cement was 72°

d. Formation temperature was 86°

e. After standing cemented for 9 hours compressive strength was 800#.

Pressure tested to 400#. Tested O.K.

f. Drilled out cement after standing cemented 12 hours.

3. Ran 3445' KB of 4-1/2" 9.5# casing and cemented with 450 sacks cement.

4. We perforated as follows: 2702'-09', 2826'-33', 3144'-51', 3263'-66', 3322'-25', 3355'-58', 3282'-86', 3329'-31'

5. Acidized from 3322' to 3358' with 3500 gallons.

Acidized from 3282' to 3266' with 3500 gallons.

Fraced from 3144' to 3161' with 30,000# sand and 30,000 gallons water.

Fraced from 2826' to 2833' with 30,000# sand and 30,000 gallons water.

Fraced from 2702' to 2709' with 30,000# sand and 30,000 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. E. Hallett

TITLE **District Superintendent**

DATE

(This space for Federal or State office use)

APPROVED BY

John C. Gray

TITLE

DISTRICT ENGINEER

DATE

AUG 3 1972

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.