

6-USGS-Roswell
1-PS-Engr.
1-LG-Foreman
1-File

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Injection Well

2. NAME OF OPERATOR
Getty Oil Company /

3. ADDRESS OF OPERATOR
P.O. Box 730 Hobbs, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit Ltr. P, 660 FSL & 660 FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐

RECEIVED
OCT 7 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE LC-029418 (b)	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Lea "C"	
9. WELL NO. 13	
10. FIELD OR WILDCAT NAME Grayburg-Jackson	
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Section 11, 17S, 31E	
12. COUNTY OR PARISH Eddy	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3952 DF	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/12/81 - Rigged up Permian Well Service. Released packer, nipped up BOP. Pulled tubing and packer. Ran bit and scrapper to 3987'. Set down on fill. Cleaned out to PBTD 3998'. Closed BOP.
9/14/81 - Circulated hole clean. Ran packer on 2 7/8" work string and set @ 3322'. Knox Service acidized w/3500 gals 15% NE FE and 40 ball sealers. Flushed w/50 bbls. max. pressure 3100#; min. pressure 2400# @ rate 3.3 BPM ISIP 2900#; 5 min. SIP 2700#; 10 min. SIP 2500#; 15 min. SIP 2400#.
9/15/81 - Ran Baker AD-1 packer on 105 jts. 2 3/8" IPC (3286'); set packer at 3298'.
9/16/81 - Circulated 140 bbls. treated water. Nipped up injection line and rigged down.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett

TITLE Area Superintendent

DATE 10/2/81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE

OCT 7 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO