	n 9-331 ay 1963)	OLITED STATES SUBSTITION OF THE INTERIOR verse side) GEOLOGICAL SURVEY						
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)						LC-056551A 8. IF INDIAN, ALLOTTEE OR TEIBE NAME	
1.	OIL KN GAS WELL	OTHER		K	ECEIVE	7. UNIT AGREEMENT N	AME	
2.	NAME OF OPERATOR		/			8. FARM OR LEASE NA	ME	
	Gulf Oil Corporation 🗸				AUG 2 5 1972	Holder "CB" (NGT-A) Fede:		
3.	ADDRESS OF OPERATOR				1315	9. WELL NO.		
	Box 670, Hobbs, New Mexico 88240				(**)	2		
4.	LOCATION OF WELL (Report location clearly and in accordance with any i See also space 17 below.) At surface				e requirements	10. FIELD AND FOOL, OR WILDCAT Grayburg Jackson		
	660' FN & WL, Section 17, 17-S, 30-E					11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA		
						Sec 17, 17-S, 30-E		
14.	, PERMIT NO.		15. ELEVATIONS (Show whether DE		', RT, GR, etc.)	12. COUNTY OR PARISI	1 13. STATE	
				3666'	GL	Eddy	New Mexico	
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data							
	NOTICE OF INTENTION TO:			1	SUBSEQUENT REPORT OF:			
	TEST WATER SHUT-OFF	P	ULL OR ALTER CASING		WATER SHUT-OFF	XX REPAIRING	WELL	
	FRACTURE TREAT	м	ULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING C	ASING	
	SHOOT OR ACIDIZE	A	BANDON*		SHOOTING OR ACIDIZING	ABANDONME	NT*	
	REPAIR WELL	c	HANGE PLANS		(Other)			
	(Other)					ts of multiple completion pletion Report and Log fo		
17.	proposed work. If well nent to this work.) *	MPLETED OPER	ATIONS (Clearly state hally drilled, give sub	all pertinent des surface locations	tails, and give pertinent date and measured and true verti	s, including estimated dat	te of starting any	
pit 46	can Drilling Com	npany sp ints and	udded 12-1/4" 1 cut ioint.	surface h	nole at 8:45 AM, A 3-5/8" OD 24# K-59	August 17, 1972	. Drilled	

Capitan Drilling Company spudded 12-1/4" surface hole at 8:45 AM, August 17, 1972. Drilled to 463'. Ran 13 joints and 1 cut joint, 452' of 8-5/8" OD 24# K-55 ST& C casing set and cemented at 463' with 150 sacks of Class C cement with 12-1/2#/sack of Gilsonite and 4% gel and 100 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC & NU 21 hours. Tested casing with 1000#, 30 minutes, OK.

Started drilling 7-7/8" hole at 463' at 6:30 PM, August 18, 1972.



		MEXICO	
18. I hereby certify that the foregoing is true and corr	ect Area Engineer	DATE August 21, 1972	
(This space for Federal or State office use)	TITLE	DATE	
APPROVED BY CONDUCTOR APPROVAL, IF ANY:		DATE	
Carrie Control	*See Instructions on Reverse Side		