

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

LC-056551A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holder CB (NCT-B) Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 9, 17-S, 30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FS & WL, Section 9, 17-S, 30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Capitan Drilling Company spudded 12-1/4" surface hole at 8:45 AM, August 30, 1972. Drilled to 498'. Ran 15 joints and 1 cut joint, 487' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 498' with 150 sacks of Class C cement with 12-1/2# Gilsonite per sack and 4% gel and 100 sacks of Class C with 2% Ca Cl₂. Found top of cement at 90'. Cemented to surface with 4 yards of ready mix. WOC & NU 18 hours. Tested casing with 1000#, 30 minutes, OK.

Started drilling 7-7/8" hole at 498' at 3:30 PM, August 31, 1972.

RECEIVED

SEP 1 1972

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

U. J. Kallinger

TITLE Area Engineer

DATE September 1, 1972

(This space for Federal or State office use)

APPROVED BY
CONDITIONS

SEP - 6 1972

H. L. BECKMAN

ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side