

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

4001 Penbrook Street, Odessa, TX 79762 915/368-1488

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL & 330' fwl OF SECTION 35, T-17-2, R-30-E

NM OIL CONS COMM  
Drawer DD  
Artesia, NM 88210

FORM APPROVED

Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 0558579

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

FEDERAL 1

9. API Well No.

30-015-21062

10. Field and Pool, or exploratory Area

GRAYBURG JACKSON

11. County or Parish, State

EDDY NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5/03/95 OBJECTIVE: PLUG AND ABANDON FEDERAL WELL NO. 1. NOTIFIED BLM 10:30 A.M. 5/03/95.

MIRU SIERRA WELL SERVICE RIG #3, NU CLASS 1 MANUAL BOPE.

PULLED 101 JTS PRODUCTION TBG. SECURE WELL, SDON.

5/04/95 GIHM/CIBP, SET @ 3048', MIX 25 SXS SALT GEL, CIRC WELL W/45 BBLS.

PUMP PLUG #1, 25 SXS CLASS C 14.8 PPG, 1.32 CFPS CMT, INTERVAL 3048'-2804', TOC @ 2804', LD 16 JTS TO 2543'.

PUMP PLUG #2, 25 SXS CLASS C 14.8 PPG, 1.32 CFPS CMT, INTERVAL 2543'-2299', TOC @ 2299', LD 81 JTS WS.

RU WL TRK & PERF @ 553'. PUMP PLUG #3, 155 SXS CLASS C 14.8 PPG, 1.32 CFPS CMT, INTERVAL 553'-3'. CEMENT CIRCULATED TO SURFACE LEAVING INSIDE OF 5-1/2" CASING FULL OF CEMENT.

RD MO SIERRA WELL SERVICE RIG #3.

WELL IS PLUGGED AND ABANDONED.

RECEIVED

Approved as to plugging for the Over 1000 ft.  
Liability under bond is retained until  
surface restoration is completed.

OIL CON. DIV.

DIST. 2

14. I hereby certify that the foregoing is true and correct

Signed

*[Signature]*

Title REGULATION SPECIALIST

Date 5/09/95

(This space for Federal or State office use)

Approved by

Title

Petroleum Engineer

Date

6/9/95

Conditions of approval, if any: