

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR. DATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole		5. LEASE DESIGNATION AND SERIAL NO. NM-0384576
2. NAME OF OPERATOR General Operating Company ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME --
3. ADDRESS OF OPERATOR Suite 1007 Ridglea Bank Building, Ft. Worth, Texas 76116		7. UNIT AGREEMENT NAME --
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FNL and 1980' FEL Section 35-T17S-R30E, N.M.P.M.		8. FARM OR LEASE NAME Stevens-Federal
14. PERMIT XX Issued: 5/22/74		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3535' GR, 3544' RKB		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson Q-SA
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 35-T17S-R30E N.M.P.M.
		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒Drilling ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

General Operating Company's Stevens Federal Well No. 1 was drilled to a total depth of 3400' RKB with a 7-7/8" bit. Total depth was reached on 5/29/74, and after logging well with Welex-GR-Compensated Density-Caliper-Guard logs, well was plugged and abandoned as a dry hole.

Per telephone approval by Mr. Jim Knauf on 5/29/74, cement plugs were placed as follows by Halliburton Company on 5/29/74:

3250' - 3350'	35 Sacks Class H
2475' - 2575'	35 Sacks Class H
1285' - 1385'	35 Sacks Class H
450' - 550'	50 Sacks Class H
Surface	10 Sacks Class H

Surface plug placed inside and outside of 10-3/4" OD surface casing and dry hole marker was set in cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. W. Stumhoffer
C. W. Stumhoffer

TITLE

Vice President

DATE

9/11/80

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) PETER W. CHESTER

TITLE

ACTING DISTRICT ENGINEER

DATE

OCT 24 1980

CONDITIONS OF APPROVAL, IF ANY: