

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

M-2747

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jackson "B"

9. WELL NO.

29

10. FIELD AND POOL, OR WILDCAT

Square Lake

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1-17S-30R

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

WINDFORD OIL COMPANY

MAY 20 1976

3. ADDRESS OF OPERATOR

Box #198, Artesia, New Mexico 88210

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO4. LOCATION OF WELL (Report location clearly and in accordance with any State law or regulation. See also space 17 below.)
At surface1980' from south and 1830' from west lines of
Section 17S-30R

RECEIVED

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

OCT 27 1976

16. Check Appropriate Box To Indicate Nature of Notice Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

ARTESIA, OFFICE SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Plug and Abandon ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On March 30, 1976, operations were started to clean out well to approximately 2156'.

By April 12, 1976, well had been cleaned out to 1236' but no further progress could

be made. On April 12, ran 2 1/2" tubing to 1236' and cemented down tubing with 750
sacks class H cement plus 150 sacks thickset cement. Squeezed off water flow.

On April 13, tested tubing with 1500 psi. for 30 minutes and pressure held.

Cemented between 2 1/2" tubing and 8-5/8" casing with 150 sacks class C cement and

left 150' cement above 8-5/8" casing shoe. Tested with 1000 psi. for 30 minutes

and pressure held. On April 15, set 10' cement plug at surface. On May 18, 1976,

ripped location, covered pits, cleaned location and installed dry hole marker.

Location is ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Consulting Engineer

DATE May 19, 1976

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

OCT 2 1976

J. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1969—O-685229

847-485

RECEIVED
OCT 27 1969
U.S. DEPT. OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
DENVER, COLORADO