

N.M.O. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ P X A

2. NAME OF OPERATOR
Amoco Production Company /

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 760' FSL X 2310' FEL, Sec. 30
AT TOP PROD. INTERVAL: (Unit 0, SW-1/4, SE-1/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒
☒

5. LEASE
LC-062407 RECEIVED
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME JUN 10 1981
8. FARM OR LEASE NAME O. C. D.
Empire South Deep Unit ARTESIA, OFFICE
9. WELL NO.
7
10. FIELD OR WILDCAT NAME
South Empire Wolfcamp
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
30-17-29
12. COUNTY OR PARISH Eddy 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3637' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon by the following procedure: *

Run cast iron bridge plug and set at approx. 7810'. Spot 35' of Class 'C' cement on top of bridge plug. Load hole with mud to within 50' of intermediate casing. Spot 10 sacks Class 'C' cement over 2844'-2944'. Load hole within 475' of surface. Spot 10 sacks of Class 'C' cement over 375-475'. Load hole with mud to within 100' of surface. Spot 10 sacks Class 'C' cement to surface. Erect P X A marker.

0+4-USGS, A 1-Hou 1-Susp 1-GPM

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED *Ann Mitchell* TITLE Admin. Analyst DATE 5-29-81

APPROVED BY
CONDITIONS OF APPROVAL

APPROVED AS AMENDED
Peter W. Chester
JUN 5 1981
JAMES A. GILLHAM
DISTRICT SUPERVISOR

(This space for Federal or State office use)

TITLE

DATE

RECEIVED
JUN 9 1981
Set @
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

* See attached
Program