

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI
(Other instructions
reverse side)

FE*
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM-0467934

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

UNIT AGREEMENT NAME

1. OIL ☒ GAS ☐ OTHER ☐
WELL WELL

2. NAME OF OPERATOR
General American Oil Company of Texas

OCT 1 1975

3. ADDRESS OF OPERATOR
P. O. Box 416 Loco Hills, New Mexico 88255 O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement to this work.)
See also space 17 below.)
At surface

660' FNL and 990' FNL Sec. 27, T-17S, R-30E

9. WELL NO.
10

10. FIELD AND POOL, OR WILDCAT
Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 27 - 17S - 30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3636 GL 3646 KB

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☒
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

Perforating

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spud well at 11:00 A.M. 9-12-75.

2. Ran 8-5/8" OD 23# casing and set at 498' KB as follows:

- Volume of cement equalled 132 cubic feet (100 sacks).
- Brand of cement was Southwestern Class "C" with 2% CaCl.
- Approximate temperature of cement slurry was 70° F.
- Formation temperature was 65° F.
- After standing cemented for 9 hours compressive strength was 800#.
Pressure tested to 400#. Tested O.K.
- Drilled out cement after standing 12 hours.

3. Ran 4-1/2" OD 9.5# casing to 3230' KB and cemented with 600 sacks cement

4. We perforated 3120'-3126' (12 holes) and 3148'-3154' (12 holes)

5. Acidized from 3120' to 3154' with 2250 gallon acid.

Fraced from 3120' to 3154' with 30,000 gallons gelled water and 20,000# acid

RECEIVED
SEP 29 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Roy Crow

TITLE **District Superintendent**

DATE **September 26, 1975**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

RECEIVED

OCT 1 1962

ARTESIAL OFFICE