

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
811 South First, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, New Mexico 87505

WELL API NO.
30-015-22154

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-8095

7. Lease Name or Unit Agreement Name

Etz C State

8. Well No.
27

9. Pool name or Wildcat
Grbg Jackson SR Q Grbg SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS).

1. Type Of Well:
OIL ☒ GAS ☐
WELL WELL OTHER

2. Name of Operator
Mack Energy Corporation /

3. Address of Operator
P.O. Box 960, Artesia, NM 88211-0960

4. Well Location
Unit Letter E : 1850 Feet From The North Line and 1315 Feet From The West Line
Section 16 Township 17S Range 30E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3687' RT

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Mack Energy Corporation proposes to plug and abandon well as follows:

1. Notify OCD 24 hours before starting plugging operations.
2. Set 25 sx cement plug 50' above and below 10 3/4" casing from 513'-413'.
3. Set 10 sx surface plug.
4. Install dry hole marker.

Perf csq. @ 990'. Place 100' of cmt. inside
& outside of csq. 890'-990' - TAG
Perf csq. @ 513'. Place 100' of
Cement inside & outside of csq. - TAG
413'-513'
Perf Both 10 3/4" 7" csq @ 60'-
Place 60' of cmt 0'-60' inside &
outside of both strings

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Crissa D. Carter TITLE Production Analyst DATE 10/21/02

TYPE OR PRINT NAME

Crissa D. Carter

TELEPHONE NO.

(This space for State Use)

APPROVED BY [Signature] TITLE Wild Sep ID DATE NOV 15 2002

CONDITIONS OF APPROVAL, IF ANY: