

NMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028775 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

F. M. Robinson Fed Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Grayburg Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

27-17S-29E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State or Federal Office
See also space 17 below.)
At surface

1825' FSL & 2220' FWL (Unit letter K)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3527' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Propose to P&A dry hole in the following manner:

1. RIH w/DP OE & spot cmt plugs w/heavy gelled mud between all cmt plugs as follows:
2. Spot 200' plug (75 sx cmt) 10,790-10,590'.
3. Spot 200' plug (75 sx cmt) 9120-8920'.
4. Spot 150' plug (75 sx cmt) 7285-7135'.
5. Spot 150' plug (55 sx cmt) 5400-5250'.
6. Spot 100' plug (40 sx cmt) 3590-3490' across 9-5/8" csg shoe.
7. Spot 10 sx cmt plug @ surface. Install regulation dry hole marker. Clean & level location per BLM stipulations for abandonment.

Prior verbal approval was obtained from USGS to P&A on 12/10/77.

RECEIVED
JAN 19 1978
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Drlg. Supt.

DATE 1/17/78

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE FEB 7 - 1978

CONDITIONS OF APPROVAL, IF ANY: