

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.  
LC-029418-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

120

10. FIELD AND POOL, OR WILDCAT

FREN 7 - RIVERS

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 14, 17S-31E

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

1. OIL ☒ GAS ☐ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR  
GETTY OIL COMPANY

3. ADDRESS OF OPERATOR  
P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
760' FSL & 760' FWL

RECEIVED

JAN 16 1978

D. C. C.

ARTESIA OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3880'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7-7/8" Hole to 2597'.

11-6-77 - Set 5-1/2" 14# Casing at 2597'.

Howco cemented w/620 sxs. Howco Lite W/6# Salt + 1/4# Flocele/Sk. and 200 Sxs. Class

"C" Cement w/2% CaCl<sub>2</sub>/Sk. Total - 820 Sxs.

Cement Circulated

Waiting on Cement 24 Hrs.

Tested 5-1/2" Casing w/1200# for 30 Minutes.

No Drop in Pressure.

RECEIVED  
JAN 12 1978  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett

TITLE AREA SUPERINTENDENT

DATE 1-9-78

(This space for Federal or State office use)

APPROVED BY Joe S. Lara  
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE JAN 13 1978