

5-USGS-ARTESIA

1-R.J. STARRAK-15th FLOOR LSA

1-A.B. CARY-MIDLAND

NMOCC COPY

Form 9-331  
(May 1963) 1-FILEUNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029418-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

FEB 7 1978

2. NAME OF OPERATOR

GETTY OIL COMPANY ✓

O.C.C.

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

660' FSL and 660' FWL

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

121

10. FIELD AND POOL, OR WILDCAT

FREN 7-RIVERS

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

23-17S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3846.5 GR

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

Drilled 7-7/8" hole to 2600'.

Set 5-1/2" 14# 8 Rd H-40 R-3 casing at 2600' on 12-18-77.

Howco cemented w/375 sks. of Howco Lite w/6# Salt and 1/4# Celloflakes/Sk. and  
200 Sks. of Class "C" Cement w/2% CaCl<sub>2</sub>. Total Cement 575 Sks.

Cement Circulated.

WOC-24 Hours.

Tested to 1200# for 30 minutes with no drip in pressure.

RECEIVED  
FEB 2 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE JANUARY 31, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

FEB 2 1978

\*See Instructions on Reverse Side