

5-USGS-ARTESIA

1-R.J. STARRAK-15 FLOOR-T 3A

1-A.B. CARY-MIDLAND

Form 9-331  
(May 1963) 1-FILE

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**NMOCG COPY**SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029418-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

**SUNDRY NOTICES AND REPORTS ON WELLS**(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposal.)**RECEIVED**1. OIL ☒ GAS ☐ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

GETTY OIL COMPANY ✓

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

**O. C. C.  
ARTESIA, OFFICE**4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FSL and 660' FWL

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

121

10. FIELD AND POOL, OR WILDCAT

FREN 7-RIVERS

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

23-17S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3846.5 GR

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 11" hole at 1:30 P.M. 12-14-77.

Drilled to 673'.

On 12-15-77 set 8-5/8" 24# 8Rd K-55 Rge 3 ST&amp;C casing @ 673'.

Howco cemented w/150 sks. Hal. Lite w/1/4# Flocele/Sk. and 150 Sks. Hal Class "C" Cement w/2% CaCl2/Sk. Total Cement 300 Sks.

Cement Circulated.

WOC - 18 Hrs.

Tested to 1000# for 30 Minutes.

No Drop in Pressure.

**RECEIVED**  
**FEB 2 1978**  
**U.S. GEOLOGICAL SURVEY**  
**ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE

January 31, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

DISTRICT ENGINEER

TITLE

DATE

FEB 2 1978

\*See Instructions on Reverse Side

/bh