

NMOCC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRICATE*
(Other instructions on reverse side)

copy to SF

Form approved.
Budget Bureau No. 42-R1424.

1-ENGR.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-029419-A	
2. NAME OF OPERATOR GETTY OIL COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. BOX 730, HOBBS, NEW MEXICO 88240		7. UNIT AGREEMENT NAME SKELLY UNIT	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1880' FNL & 1880' FEL, SECTION 22		8. FARM OR LEASE NAME	
14. PERMIT NO.		9. WELL NO. 124	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3848' GR		10. FIELD AND POOL, OR WILDCAT FREN 7-RIVERS	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 22-17S-31E	
		12. COUNTY OR PARISH EDDY	13. STATE N.M.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐
☐

FRACTURE TREATMENT

REPAIRING WELL

SHOOTING OR ACIDIZING

ALTERING CASING

(Other)

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 2550'. Set 5-1/2" 14# J-55 8 RT SS casing at 2550'. Cemented with 470 sacks 50/59 Poz-Mix; 6# Salt/Sack; 1/4# Cello Flakes with 4% Gel; and 200 sacks Class "C" with 2% CaCl₂. Cement circulated to surface. WOC 24 hrs. Tested 5-1/2" casing with 1500# for 30 minutes. No drop in pressure.

RECEIVED

NOV 4 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE

November 2, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE

NOV 10 1977

*See Instructions on Reverse Side