

NMOC CCY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029420-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

UNIT LTR. M, 560' FSL AND 760' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3843' GR

9. WELL NO.

126

10. FIELD AND POOL, OR WILDCAT

FREN SEVEN RIVERS

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

15-17S-31E

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 11" hole 10-18-77. Drilled to 575'. Set 8-5/8" 24# K-55 Casing at 575'.

Dowell cemented with 125 sxs. 50/50 Pos Mix with 4% D20 Bentonite &amp; 1/4# Cello Flakes/Sx.

and 125 Sxs. Class "C" Cement with 2% Ca Cl<sub>2</sub>/Sx. Cement circulated. Tested 8-5/8"

casing with 1200# for 30 minutes; no drop in pressure.

RECEIVED

DEC 12 1977

U.S. GEOLOGICAL SURVEY  
ARTESIA, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE AREA SUPERINTENDENT

DATE 12-7-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE

DEC 21 1977

\*See Instructions on Reverse Side

/bh

