

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028793-c

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

RECEIVED

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR

General American Oil Company of Texas

DEC 15 1978

8. FARM OR LEASE NAME

Grayburg Deep Unit

3. ADDRESS OF OPERATOR

P. O. Box 128, Loco Hills, New Mexico 88255

O. C. C.

9. WELL NO.

#8

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

10. FIELD AND POOL, OR WILDCAT

Loco Hills Morrow

1980' FNL and 760' FEL of Section 30, T. 17-S, R. 30-E

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T-17-S, R-30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3584.4 GR

12. COUNTY OR PARISH

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well November 17, 1978 at 7 AM.

Ran 11 3/4" 42# H-40 casing and set at 504' KB. Cemented with 325 sacks H. L. cement with 1% CaCl and 300 sacks Class C cement with 2% CaCl. Pressure tested casing to 1000#. Tested OK.

Ran 8 5/8" 32# K-55 casing and set at 3517' KB. Cemented with 750 sacks Class H cement with 10# sand and 5# salt, 1/2 of 1% CFR-2, 1/4# Flocele per sack. Pressured tested casing to 2000#. Tested OK.

RECEIVED  
DEC 13 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Rendall Hawkins

TITLE Asst. Field Superintendent

DATE December 12, 1978

(This space for Federal or State office use)

APPROVED BY Joe J. Lara

TITLE ACTING DISTRICT ENGINEER

DATE DEC 13 1978

CONDITIONS OF APPROVAL, IF ANY: