

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other Instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18299

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Indio

7. UNIT AGREEMENT NAME

1 1980

8. FARM OR LEASE NAME

Federal I-COBLA OFFICE

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat-Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

5-17-30

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P.O. Drawer A, Levelland, Texas 79336

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

660' FSL & 1980' FEL, Sec 5 (SW $\frac{1}{4}$ , SE $\frac{1}{4}$ )

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3691.2 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>

PULL OR ALTER CASING

<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>

REPAIRING WELL

<input type="checkbox"/>
<input type="checkbox"/>
<input checked="" type="checkbox"/>

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to TD of 11150' on 6-18-78. Evaluated logs and drill stem tests and determined well not commercially productive. Plugged and abandoned as follows:

Spotted 60 sacks Class H cement 10350' - 10500'.

Spotted 60 sacks Class H cement 9275' - 9425'.

Spotted 60 sacks Class H cement 7800' - 7950'.

Spotted 60 sacks Class H cement 6510' - 6660'.

Spotted 40 sacks Class H cement 4800' - 4900'.

Spotted 40 sacks Class H cement 3150' - 3250'.

Spotted 10 sacks Class H cement at the surface.

Released rig 5:00 PM 6-21-78. Erected abandonment marker.

RECEIVED

SEP 1 1978

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray W. Cox

TITLE

Admin. Supervisor

DATE

8/25/78

(This space for Federal or State office use)

APPROVED BY

(C. S. S.) ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 29 1980

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-A

1-Div

1-Susp

1-Dorchester Explo

\*See Instructions on Reverse Side

Attn: Chuck Monahan