

MOCC COPY

Copy to 87

Form 9-551
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved,
Project Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. ☐ NEW WELL ☐ EXISTING WELL ☐ OTHER		2. NAME OF OPERATOR Hall Energy, Inc. ✓		MAY 22 1978		3. ADDRESS OF OPERATOR Box 954, Artesia, New Mexico 88210		O. C. C. ARTESIA, OFFICE		4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 340 FWT and 340 FWT		5. LEASE DESIGNATION AND SERIAL NO. 20 060 30		6. IF INDIAN, ALLOTTEE OR TRIBE NAME		7. UNIT AGREEMENT NAME		8. FARM OR LEASE NAME McIntosh		9. WELL NO.		10. DRILL AND POOL, OR WILDCAT		11. SEC., T. R., M., OF BLK. AND SURVEY OF AREA Sec. 22 T-17N R-30E		12. COUNTY OR PARISH		13. STATE N.M.	
14. PERMIT NO.		15. ELEVATIONS (Show whether br, ri, or, etc.) 360.00																											

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

FIRST WATER SHUT-OFF

PILL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE P.L.S.

(Other)

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DEVELOPMENT PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 3:00 P.M., April 28, 1978. Ran 479 feet, 8 5/8 24 lbs. K-11. Cement with 175 sacks of class C, 2 1/2 cu ft. Circulate 48 sacks to plug, plug down at 2:50 P.M., April 29, 1978, and pressured 2137 feet. After waiting 18 hours, drill to 3450 feet and set 2137 feet K-40 SUC 14 lbs., 1310 feet J-55 1 1/2 lbs. LTC. Cement with 250 sacks of class C, 2 1/2 cu ft and 380 sacks of class H, 5 lbs of salt, 10 lbs. of no. 3 sand, and pressure to 1500 lbs.

RECEIVED

MAY 18 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Loyd

TITLE

Superintendent

DATE

5-17-78

(This space for Federal or State office use)

APPROVED BY

Joe D. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 19 1978

CONDITIONS OF APPROVAL, IF ANY:

*See instructions on Reverse Side